

## HANDSFREE TALKBACK DOOR PLATE SPEAKER MODEL V-1072A-ST, V-1072A-BRASS, V-1073

### FEATURES:

UTILIZES CAT 3/5/5E/6 TWISTED TELEPHONE/DATA CABLE

STAINLESS STEEL CONSTRUCTION (V-1072A-ST)

BRASS CONSTRUCTION (V-1072A-BRASS)

11 AWG STEEL PAINTED FACEPLATE (V-1073)


45 OHM INPUT IMPEDANCE

WEATHER RESISTANT

VANDAL RESISTANT (V-1073)

CALL SWITCH BUTTON

SCREW TERMINALS FOR ALL CONNECTIONS



### DESCRIPTION:

**V-1072A-ST** - Durable brushed stainless door plate speaker with call button. The unit provides handsfree talkback capability from an outside entry or doorway when used with the Valcom Door Entry Management and Intercom Systems. The unit features a water resistant 2 inch speaker and corrosion resistant hardware.

**V-1072A-BRASS** - Durable brass door plate speaker with call button. The unit provides handsfree talkback capability from an outside entry or doorway when used with the Valcom Door Entry Management and Intercom Systems. The unit features a water resistant 2 inch speaker and corrosion resistant hardware.

**V-1073** - Vandal-Resistant door entry speaker with call button. The unit provides handsfree talkback capability from an outside door or entryway when used with the Valcom Door Entry Management and Intercom Systems. Screw terminals are provided for switch connections. Heavy duty steel pushbutton with internal louvered speaker. The speaker is weather resistant for both outdoor and indoor installations. Faceplate constructed from painted 11 AWG Steel.

### SPECIFICATIONS:

#### SPEAKER

45 Ohm

#### SWITCH

Single Pole Momentary Contact

#### ENVIRONMENT:

Suitable for Indoor or Outdoor Installations

#### MOUNTING: V-1072A-ST, V-1072A-BRASS

Mounts in a double gang (4" x 4") electrical box

#### MOUNTING: V-1073

Mounts in a 2-gang (4" x 4") electrical box with one-way screws

#### DIMENSIONS AND WEIGHT:

##### V-1072A-ST, V-1072A-BRASS

4.5" (11.43 cm) H x 4.5" (11.43 cm) W x 1.3" (3.3 cm) D

Weight: .55 lb. (.25 kg)

#### DIMENSIONS AND WEIGHT:

##### V-1073

4.5" (11.43 cm) H x 4.5" (11.43 cm) W x 1.75" (4.45 cm) D

Weight: 1.68 lb. (.76 kg)

# ARCHITECTS' AND ENGINEERS' SPECIFICATIONS MODEL V-1072A-ST, V-1072A-BRASS, V-1073 HANDSFREE TALKBACK DOOR PLATE SPEAKERS

The Talkback Door Plate Speaker, Model V-1072A-ST, shall be a weather resistant speaker assembly for use with handsfree talkback control units. It shall have a voice coil rating of 45 Ohms. The faceplate assembly shall be constructed of rugged stainless steel. It shall have a call button for signalling. The unit shall be compatible with 2-gang 4" x 4" electrical boxes. Dimensions shall be 4.5" (11.43 cm) H x 4.5" (11.43 cm) W x 1.3" (3.3 cm) D and the unit shall weigh .55 lb. (.25 kg).

The Talkback Door Plate Speaker, Model V-1072A-BRASS, shall be a weather resistant speaker assembly for use with handsfree talkback control units. It shall have a voice coil rating of 45 Ohms. The faceplate assembly shall be constructed of brass. It shall have a call button for signalling. The unit shall be compatible with 2-gang 4" x 4" electrical boxes. Dimensions shall be 4.5" (11.43 cm) H x 4.5" (11.43 cm) W x 1.3" (3.3 cm) D and the unit shall weigh .55 lb. (.25 kg).

The Vandal Resistant Talkback Door Speaker, Model V-1073, shall be a weather resistant speaker assembly for use with handsfree talkback control units. It shall have a voice coil rating of 45 Ohms. It shall have a call button for signaling. The faceplate shall be constructed of 11AWG steel. The unit shall be compatible with 2-gang 4" x 4" electrical boxes. The unit shall measure 4.5" (11.43 cm) H x 4.5" (11.43 cm) W x 1.75 (4.45)" D and the unit shall weigh 1.68 lb. (.76 kg). The unit shall be connected using standard two pair CAT 3/5/5E/6 telephone/data cable.

## Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened.  
(A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs  
(major repairs will be subject to additional charges for parts and labor).

**This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.**

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.